

PM5 DIGITAL WEIGHT INDICATOR



1,000,000 Internal resolution
Weight reading stable up to
50,000 divisions

Aluminium
die casting casing

Vacuum fluorescent
type display



- 13 mm 7 digits vacuum fluorescent display
- 1 part in 100,000 display resolution
- 1 part in 1,000,000 internal resolution
- 1, 2, 5, 10 selectable display increment size
- 0 to 4 decimal point selectable
- Input signal 0 to 20 mV
- A/D 24 bit sigma-delta conversion
- 5 VDC up to 8 X 350 load cell excitation
- -10 to 40 degrees C operating temperature
- Two channel RS232 port
- Sealed membrane keyboard
- Digital calibration and set-up from keyboard
- 220 VAC 50Hz 0.25A power requirement

Available models

PM5-S standard model

additional to standard specification

- Opto-isolated RS232

PM5-U USB model

additional to standard specification

- One USB port

PM5-M memory model for truck scale

additional to standard specification

- 900 transaction store memory
 - Direct connect to ticket printer
- Print : truck ID, date, time, CN, gross, tare, net, unit price,
total price, % loss, owner name heading in Thai and
report

Accessories

D2001 remote display



1 inch high 5 digits red bright
7 segment LED

D2002 remote display



90 mm high 5 digits with "-" double row
supper bright LED

D2003 remote display



2.3 inch high 5 digits red bright
7 segment LED

Load cell junction box



4 or 6 load cells stainless steel junction
box

